


Technical Data Sheet

Date of Issue 08/06/2023

Rev. 04_21/05/2025

T207

Painter's Superior Masking Tape



Product Description

Painter's Superior, medium adhesion masking tape characterized by a regular crepe paper backing and a natural rubber adhesive. Universal and versatile, it is suitable for masking indoor operations, for bundling, holding, splicing and marking activities and for light non – critical spray painting activities at moderate temperature (max 60°C up to 30 min).

Special colour backing improves visibility during the paint and masking process for easy and clean removal.

FSC® and PEFC certified masking tapes available on demand.

Features

- Medium adhesion
- Good holding power
- Good contact on multiple surfaces
- Good paint anchorage
- Quick stick
- Clean removal in warm environments without breaking

Main Applications

- Masking and painting in homemade and professional operations (no UV exposure recommended)
- Non -critical spray painting operations at medium temperature

Technical Data

	Metric	Imperial Units	Test Method
Total weight*	92 g/m ²	92 g/m ²	ISO 536
Total thickness*	130 µm	5.1 mils	Internal
MD tensile strength*	38 N/cm	21.7 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break*	8 %	8 %	AFERA 5004/PSTC 131
Adhesion to steel plate*	2.0 N/cm	17.9 oz/in	AFERA 5001/PSTC 101
Service temperature	up to 60°C	up to 140°F	

Backing material
Saturated crepe paper

Type of adhesive
Natural rubber

*Typical value

Available colour



White Yellow

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. TTPL reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. TTPL does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.