TECHNICAL DATA SHEET

Date of Issue 11/10/2016 | Rev. 08_10/2026

T402
Carton Sealing Standard
Paper Packaging Tape



Recycling-friendly tape according to INGEDE Method 12

PRODUCT DESCRIPTION

Carton Sealing Standard Paper packaging tape with a natural rubber adhesive designed to seal cartons and light weight boxes. Easy to unwind and hand tearable, it provides a good hold on the application surface, even in warm environments. T402 can be disposed together with the packaging on which it is applied without affecting the paper and cardboard recycling process, in accordance with INGEDE procedure.
FSC® certified masking tapes available on demand.

FEATURES

- Medium adhesion
- Excellent holding power
- Hand tearable
- Good contact on cardboard
- Resistant to shocks
- Recycling-friendly tape according to INGEDE Method 12
- FSC® certified masking tapes available on demand

MAIN APPLICATIONS

- Light duty carton sealing
- Manual packaging
- Non - critical bundling, splicing and holding

CONSTRUCTION

	Adhesive	Backing
Material	Natural rubber	Saturated crepe paper
Colour	Transparent	Brown White

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Total weight	89 g/m²	2.62 oz/yd²	ISO 536
Total thickness	120 µm	4.7 mils	Internal
MD tensile strength	35 N/cm	20 lb/in	AFERA 5004/PSTC 131
MD elongation at break	7 %	7 %	AFERA 5004/PSTC 131
Adhesion to steel plate	2.4 N/cm	21.9 oz/in	AFERA 5001/PSTC 101

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use
All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life
Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.